

Using industry

KIOSK、Gaming、Automation
terminal、Vending machine
Medical

- * SVGA(1920x1080) 400cd/m2
- * VGA & HDMI Signal Input
- * IR Touch Screen
- * Multi Touch Technology (4 points)
- * OSD Control on the Back Cover
- * 220V Power Input
- * Rugged Industry Design
- * Support Embedded Mounting

Specifications

LCD Panel

Panel Type	AUO LCD Panel
Resolution(Pixel)	1920 x 1080
Display Area (mm)	H: 698.4 x V: 392.85
Brightness (nit)	400 nits
Contrast Ratio	1200:1
Colors	16.7M
View Angle(U/D/L/R)	89°/89°/89°/89°
Backlight Lifetime	30,000 hours
OSD Control	Auto, Menu, Left, Right, Exit, Power

Touch Panel

Type	IR Touch Technology
Resolution	4096 x 4096
Transmittance	92%±2%

Interface

Signal Input	15Pin D-Sub VGA + HDMI
Touch Connector	USB

Power

Power Input	220V
Power Consumption	≤48W

Mechanical

Material	High Strength Cold Rolling Steel Chassis
Mounting	Top/Bottom and Left/Right Ø6-Ø12 holes VESA 100mm x 100mm Mount VESA 150mm x 150mm Mount Support Embedded Mounting

Dimensions(mm)	779.7(W) x 494.3(H) x 68(D)
----------------	-----------------------------

Environment

Operating Temp.	-10°C ~ 50°C
Storage Temp.	-20°C ~ 60°C
Relative Humidity	10 ~ 90% @ 40°C Non-condensing
Vibration	1G peak, 5 ~ 500Hz(Random)
Shock	15G peak Acceleration (11msec.duration)
Rating	Facilitate Installation of the Demolition

Option

Privacy	3M or other Brand Privacy Filter
---------	----------------------------------

