



ShenZhen ITCF technology Co., Ltd

Add: 3rd floor, C building, Fu Wen Industry Park, Busha Road, BuJi, shenzhen, CHINA

Tel: 86-755-82207646

Mobile Phone: 86-13266540012

Email: salesmanager@ismade.com

www.itcfpos.com

Features

- Easy access OS to proceed maintainance
- Fexible configuration available
- Durable and stable metal base
- MSR and Customer Display Available
- Aluminium alloy housing



ITCF-199TPA 13

Motherboard	
CPU	Intel I3 3217 CPU Duo core 1.8GHz,Support turbo boost 2.6G
chipset	CPU Integrated
System Memory	1x DDR3 SO-DIMM 1333/1600MHZ 8GB
Storage	64G SSD
LAN	RealTek 8111E Gigabit Ethernet
Audio	RealTek ALC662 HD audio decode
LCD touch panel	
LCD size	15''
Touch screen	5-wire capacitive touch screen,USB interface
Resolution	XGA 1024*768
Brightness	250cd /m ²
Response	10ms
Tilting Angle	0-90 degrees
External I/O ports	
Serial ports	2*DB9 (COM1,COM2) DC5V/12V jumper optional on PIN1
USB	1*USB 3.0 5*USB 2.0
Ethernet	1*RJ45 10/100/1000Mbps
VGA	1*DB15 2nd display VGA connector
Audio	1*line out 1*Mic in
Parallel port	1*HDMI
DC port	1*12V/5A DC input for pos power source
Environmental	
Relative Humidity	20 % ~80 % Non-condensing
Operating Temperature	0 °C to 40°C
Electrical(external power adptor)	
input	100V-240V,50-60HZ 1.5A
output	DC 12V/5A
Mechanical	
Color	Black or white or golden
Packing dimension	415*290*485
Package: carton box with Foam packaging	NW: 8.5KG GW:10KG
Optional Accessories	
Customer display(VFD or LCD), MSR ,WIFI	