



ShenZhen ITCF technology Co., Ltd

Add: 3rd floor, C building, Fu Wen Industry Park, Busha Road, BuJi, shenzhen, CHINA

Tel: 86-755-82207646

Mobile Phone: 86-13266540012

Email: salesmanager@ismade.com

www.itcfpos.com

Features

- Slim plastic housing design
- Water/dusty/smoky proof
- Durable and stable metal base
- USB touch interface



ITCF-120TM

LCD Touch panel	
LCD Panel size	12.1 inch
Pixel pitch	0.24(H)×0.24(V) mm
Display area	245.8(H)×184.5(V) mm
Contrast	700:1
View Angle	Horizontal: 160; Vertical: 145
Tilting Angle	0-90 degrees
Display color	16.2M
Resolution	XGA 1024*768 @ 75Hz
Brightness	250cd /m ²
Response	10ms
Touch screen	5 wire resistive touchscreen,USB interface
Rear I/O ports	VGA: 15-pin-D-SUB, USB B type touch ,12VDC Jack in
Control Panel	Power, auto adjust, menu, up, down,
On screen Display	Brightness, The brightness, contrast, automatic adjustment, phase, clock, vertical position, horizon position, sharp than degrees, color temperature, language
Environmental	
Relative Humidity	20 % ~80 % Non-condensing
Operating Temperature	0 °C to 40 °C
Electrical	
Power Consumption	20W(max)
	Power saving mode 1W(Max)
EMI/ Product Safety	TUV,CE,VCCI,FCC
Mechanical	
Color	black
Packing dimension	325×133×305mm
Package: carton box with Foam packaging	NW:1.6KG GW: 2.4KG
Accessories	
AC Power Cable	North American and European power cables included; Other regions available upon request.
Power adaptor	100-250V/50-60HZ AC power input ,DC 12V/1.5 output
Driver CD	1*CD disk for touch function
other function cable	VGA cable USB B type cable for touch