



ShenZhen ITCF technology Co., Ltd

Add: 3rd floor, C building, Fu Wen Industry Park, Busha Road, BuJi, shenzhen, CHINA

Tel: 86-755-82207646

Mobile Phone: 86-13266540012

Email: salesmanager@ismade.com

www.itcfpos.com

Features

- Easy access OS to proceed maintainance
- Fanless and Silent
- Flexible configuration available
- Durable and stable metal base
- 15" 2nd Display monitor available



ITCF-197TPD

Motherboard	
CPU	Intel Bay Trail CPU Celeron quad core J1900 2.0GHz
chipset	CPU Integrated
System Memory	1x DDR3 SO-DIMM up to 8GB (default 2GB)
Storage	16G / 32G / 64G /128G SSD (default 32GB)
LAN	RealTek 8111E Gigabit Ethernet
Audio	RealTek ALC661 HD audio decode
LCD touch panel	
LCD size	15"
Touch screen	5-wire resisitive touch screen,USB interface
Resolution	XGA 1024*768
Brightness	250cd /m ²
Response	10ms
Tilting Angle	0-90 degrees
Second display monitor	
monitor	15" Lcd monitor w/o touch function
External I/O ports	
Serial ports	2*DB9 (COM1,COM2) DC5V/12V jumper optional on PIN1
USB	1*USB 3.0 5*USB 2.0
Ethernet	1*RJ45 10/100/1000Mbps
VGA	1*DB15 2nd display VGA connector
Audio	1*line out 1*Mic in
Parallel port	1*HDMI
DC port	1*12V/5A DC input for pos power source
Environmental	
Relative Humidity	20 %~80 % Non-condensing
Operating Temperature	0 °C to 40°C
Electrical(external power adptor)	
input	100V-240V,50-60HZ 1.5A
output	DC 12V/5A
Mechanical	
Color	white
Packing dimension	460*350*450mm for 15/15
Package: carton box with Foam packaging	NW:11KG GW:13.5KG