

Using industry

KIOSK, Gaming, Automation
termina, Medical, ATM

- * SVGA(1024x768) 400cd/m2
- * VGA & DVI Signal Input
- * Projected Capacitive Touch Screen
- * Multi Touch Technology (10 points)
- * OSD Control on the Back Cover
- * DC 12V Power Input
- * Rugged Industry Design
- * Support Embedded Mounting

Specifications

LCD Panel

Panel Type	AUO LCD Panel
Resolution(Pixel)	1024x 768
Display Area (mm)	H: 304.128 x V: 228.096
Brightness (nit)	400 nits
Contrast Ratio	1000:1
Colors	16.2M
View Angle(U/D/L/R)	80°/80°/80°/80°
Backlight Lifetime	50,000 hours
OSD Control	Auto, Menu, Left, Right, Exit, Power

Touch Panel

Type	Projected Capacitive Touch Technology
Resolution	4096 x 4096
Transmittance	87%±2%

Interface

Signal Input	15Pin D-Sub VGA + DVI-I
Touch Connector	USB

Power

Power Input	DC12V, 4.17A, DC Jack 2.0mm
Power Consumption	<=40W

Mechanical

Material	High Strength Cold Rolling Stell Chassis
Mounting	Left/Right Ø4.5 holes Support Embedded Mounting

Dimensions(mm)	352(W) x 261.5(H) x 47(D)
----------------	---------------------------

Enviroment

Operating Temp.	-20°C ~ 60°C
Storage Temp.	-30°C ~ 70°C
Relative Humidity	10 ~ 90%@40°C Non-condensing
Vibration	1G peak, 5~500Hz(Random)
Shock	15G peak Acceleration (11msec.duration)
Rating	Facilitate Installation of the Demolition

Option

Privacy	3M or other Brand Privacy Filter
Handwriting	The original handwriting handwritten input

