



ShenZhen ITCF technology Co., Ltd

Add: 3rd floor, C building, Fu Wen Industry Park, Busha Road, BuJi, shenzhen, CHINA
Email: salesmanager@ismade.com www.itcfpos.com

Features

- Easy access OS to proceed maintainance
- Fanless and Silent
- Flexible configuration available
- Durable and stable metal base



ITCF-170TP

Motherboard	
CPU	Intel Bay Trail CPU Celeron Quad core J900 2.0GHz
chipset	CPU Integrated
System Memory	1x DDR3 SO-DIMM up to 8GB (default 2GB)
Storage	16G / 32G / 64G SSD or 320G HDD /500G HDD (default 32GB SSD)
LAN	RealTek 8111E Gigabit Ethernet
Audio	RealTek ALC661 HD audio decode
LCD touch panel	
LCD size	17"
Touch screen	5-wire resisitve touch screen or multiple-dot capacitive touch screen
Resolution	SXGA 1280*1024
Brightness	3000cd /m ²
Response	10ms
External I/O ports	
HDMI	1*HDMI
USB	1*USB 3.0 3 *USB 2.0
Ethernet	2*RJ45 10/100/1000Mbps
VGA	1*DB15 2nd display VGA connector
Audio	1*line out 1*Mic in
DC port	1*12V/5A DC input for pos power source
Environmental	
Relative Humidity	20 %~80 % Non-condensing
Operating Temperature	0 °C to 40°C
Electrical(external power adptor)	
input	100V-240V,50-60HZ 1.5A
output	DC 12V/5A
Mechanical	
Color	
Packing dimension	
Package: carton box with Foam packaging	